

kleen®

PET Products by KINETICS

kleen Panel Absorptive Panel

ORIGIN – the building blocks of the kleen lineup.

The unpainted canvas of building design and acoustical treatment. These 48" x 96" panels come in a variety of thicknesses and a plethora of colors that can be cut to meet your project needs. Get creative!



KINETICS Noise Control®

What is kleen?

The kleen family of products feature recycled PET, offering ultra-low VOC emissions and bleach cleanability. The material is formaldehyde free and 100% recyclable. kleen balances acoustical design with an emphasis on environmental wellness. Harmony you can see and hear.

kleen Panel Absorptive Panel

FEATURES

- Resists mold, mildew & bacteria
- High tackability
- Impact resistant
- Hypoallergenic, dust-free & formaldehyde-free
- Easy to handle & simple to apply

COMPOSITION

- 100% Polyethylene Terephthalate (PET)
- 55% recycled content

ENVIRONMENTAL FACTORS

- 100% recyclable
- No formaldehyde VOC emissions
- ASTM – D5116
- LEED credit applicable

SPECIFICATIONS

Height:
48"

Width:
96"

Thickness Options:
3/8" / 1/2"

Weight per Square Foot:
3/8" — .27 lb.
1/2" — .44 lb.

Quantity per Box:
3/8" — 12 sheets per box
1/2" — 10 sheets per box

Fire Rating:
ASTM E-84, Class A

Red List Free
Declare.
berkeley analytical COMPLIANCE TESTED
clearchem

ACOUSTICAL DATA

Frequency (Hz)	125	250	500	1K	2K	NRC	SAA
Panel (3/8")	.04	.04	.16	.40	.63	.30	.32
Panel (3/8" w/ 2" spacer)	.07	.13	.42	.79	.89	.55	.56
Panel (3/8" w/ 4" spacer)	.14	.32	.73	.92	.72	.65	.68
Panel (1/2")	.01	.07	.26	.54	.78	.40	.41
Panel (1")	.07	.28	.63	.87	.99	.70	.69
Panel (2")	.31	.58	1.08	1.11	1.04	.95	.93

Tested following ASTM C423 using "A" and "F" mounting

KINETICS Noise Control
kineticsnoise.com/kArrow
sales@kineticsnoise.com
1.800.959.1229
A CATALYST ACOUSTICS GROUP BRAND

Kinetics Noise Control, Inc. is continually upgrading the quality of our products.
We reserve the right to make changes to this and all products without notice.